




CONSTRUCTION		APPLICATION
Conductor	Annealed copper, Bunch stranded Sizes 0.5 mm <sup>2</sup> up to 2.5 mm <sup>2</sup>	For used in dryroom for small indoor electrical appliances such as desk-lamp, radios, fans, etc.
Insulation	Polyvinyl chloride (Any colours as requested)	
CLASSIFICATION		REFERENCE
Maximum conductor temperature 70°C Circuit voltage does not exceed 300 volts.		 TIS 11-2531 TABLE 10 *Testing Voltage: 2,000 volts

RWW-VFF	Nominal cross sectional area	Min. Number & Max. diameter of wire	Thickness of insulation	Overall dimension	Allowable ampacities Free Air 40°C	Minimum insulation resistance at 70°C	Cable weight (approx.)	Standard Packing	
									PRODUCT CODE
C10026005*	2 x 0.5	0.5	28/0.16	0.8	3.2x6.2	11	0.0160	22	100/C
C10026005	2 x 0.5	0.5	16/0.21	0.8	3.2x6.2	11	0.0160	22	100/C
C10026075*	2 x 0.75	0.75	42/0.16	0.8	3.4x6.6	14	0.0140	28	100/C
C10026075	2 x 0.75	0.75	24/0.21	0.8	3.4x6.6	14	0.0140	28	100/C
C10026001	2 x 1	1	32/0.21	0.8	3.6x7.0	16	0.0127	33	100/C
C10026501	2 x 1.5	1.5	30/0.26	0.8	3.9x7.6	21	0.0111	44	100/C
C10026502	2 x 2.5	2.5	50/0.26	0.8	4.8x9.4	29	0.0092	65	100/C

C = Packing in coil  
R = Packing in reel